## NSN 5910-01-277-7060



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-277-7060 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.378 inches **Body Diameter:** 0.335 inches **Body Length:** 0.866 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 3.0 **Electrical Polarization:** Polarized **End Application:** 6625-01-212-3679 generator, sweep **Capacitance Value Per Section:** 47.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 63.0 dc single section **Tolerance Range Per Section:** -10.00/+50.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum Dc Leakage At Reference Temp: 3.000 microamperes **Terminal Surface Treatment:** 

Solder

Case Insulation Material:
Plastic

Terminal Type And Quantity:
2 uninsulated wire lead

## NSN 5910-01-277-7060

Electrolytic Fixed Capacitor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0