NSN 5910-01-279-3683

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-279-3683

| Body Style: |
|--|
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.500 inches |
| Body Diameter: |
| 0.453 inches |
| Body Length: |
| 0.875 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| End Application: |
| Aircraft, orion p-3; support equipment, f-15 aircraft |
| Insulation Resistance At Maximum Operating Temp: |
| 2000.0 megohms |
| Capacitance Value Per Section: |
| 0.390 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 200.0 dc single section |
| Tolerance Range Per Section: |
| -2.00/+2.00 percent single section |
| Case Material: |
| Metal |
| Insulation Resistance At Reference Temp: |
| 200000.0 megohms |
| Terminal Surface Treatment: |
| Solder |
| Dielectric Material: |
| Paper and plastic |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5910-01-279-3683

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| | | | on: | |
|--|--|--|-----|--|
| | | | | |

No

Fiig:

A010b0