

View Online at <https://aerobasegroup.com/nsn/5910-01-279-4411>

**Body Style:**

Dual inline

**Reliability Indicator:**

Not established

**Terminal Length:**

0.120 inches

**Body Length:**

0.200 inches

**Body Width:**

Between 0.240 inches and 0.280 inches

**Body Height:**

0.240 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.090 inches and 0.110 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.325 inches and 0.375 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**End Application:**

7025-01-192-9981 multiplexer-pow

**Section Quantity:**

2

**Capacitance Value Per Section:**

22.000 microfarads all sections

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

15.0 dc all sections

**Tolerance Range Per Section:**

-10.00/+10.00 percent all sections

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.000

**Dc Leakage At Reference Temp:**

1.000 microamperes

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

81349-mil-c-49137 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 printed circuit

**Specification Data:**

81349-mil-c-49137/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0