NSN 5910-01-279-5865

Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-279-5865

Body Style: Wo mtg facilities, axial terminals Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Terminal Longth: 1.625 inches Body Diameter: 0.562 inches Body Diagnam Designator: No common or grounded electrode (s) Capacitance Value Per Section: 8.000 nanofrands single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Ontinuous Voltage Rating And Type Per Section: 100.0.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Tolerance Range Per Section: -10.00/+10.00 pe	
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Terminal Length: 1.625 inches Body Jeimeter: 0.562 inches Body Jeimeter: 0.562 inches Body Length: 1.625 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 8.000 nanofardas single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Tose Material: Metal Test Data Document: 81349-mile-of-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Sheft Life: N/a Unit Of Measure:	Body Style:
Established Reliability Failure Rate Level in Percent: 0.100 Terminal Length: 1.625 inches Body Diameter: 0.562 inches Body Length: 1.625 inches Body Length: 1.625 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 80.000 nanotarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0.0 dc single section 100.0.0 dc single section 100.0 dc single section 100.0 recent single section Case Material: Metal Test Data Document: 81349-mile-of-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:	W/o mtg facilities, axial terminals
Reliability Failure Rate Level in Percent: 0.100 Terminal Length: 1.625 inches Body Diameter: 0.562 inches Body Length: 1.625 inches Body Length: 1.625 inches Body Length: 1.625 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 68.000 nanofarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:	Reliability Indicator:
7.100 Terminal Length: 1.625 inches 8 Body Diameter: 1.625 inches 8 Body Length: 1.625 inches 8 Body Length: 1.625 inches 8 Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 8.600 nanofaradad Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.00 de single section Tolerance Range Per Section: -1.0.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mile-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average', '", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Established
Terminal Length: 1.625 inches Body Diameter: 0.562 inches Body Length: 1.625 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 68.000 nanofarads single section 68.000 nanofaradd Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 de single section Tolerance Range Per Section: 1000.0 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Reliability Failure Rate Level In Percent:
1.625 inches Body Diameter: 0.562 inches Body Length: 1.625 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 68.000 nanofarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.100
Body Diameter: 0.562 inches Body Length: 1.625 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 68.000 nanofarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
0.562 inches Body Length: 1.625 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 80.000 nanofarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.625 inches
Body Length: 1.625 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 68.000 nanofarads single section Monderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications. reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
1.625 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 68.000 nanofarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 do single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	0.562 inches
Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 68.000 nanofarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Body Length:
No common or grounded electrode (s) Capacitance Value Per Section: 68.000 nanofarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.625 inches
Capacitance Value Per Section: 68.000 nanofarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Schematic Diagram Designator:
68.000 nanofarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	No common or grounded electrode (s)
Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Capacitance Value Per Section:
Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	68.000 nanofarads single section
Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Nonderated Operating Temp:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	Between -65.0 degrees celsius and 125.0 degrees celsius
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Nonderated Continuous Voltage Rating And Type Per Section:
-10.00/+10.00 percent single section Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1000.0 dc single section
Case Material: Metal Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tolerance Range Per Section:
Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-10.00/+10.00 percent single section
Test Data Document: 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Case Material:
81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Metal
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	2 uninsulated wire lead
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A010b0	Fiig:
	A010b0