Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-280-9143

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.000

### **Terminal Length:**

1.500 inches

**Body Diameter:** 

0.135 inches

**Body Length:** 

0.286 inches

**Terminal Diameter:** 

0.020 inches

### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

### **Capacitance Value Per Section:**

2.200 microfarads single section

## Nonderated Operating Temp:

125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

## **Capacitive Electrode Material:**

Tantalum

### **Test Data Document:**

81349-mil-c-39003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

2 uninsulated wire lead

### **Specification Data:**

81349-mil-c-39003/01 government specification

### Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A010b0