

View Online at <https://aerobasegroup.com/nsn/5910-01-281-0479>

**Body Style:**

W/mtg bracket, axial terminals

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

1.000

**Terminal Length:**

Between 1.625 inches and 2.625 inches

**Body Diameter:**

Between 0.665 inches and 0.685 inches

**Body Length:**

Between 1.844 inches and 1.906 inches

**Terminal Diameter:**

Between 0.031 inches and 0.036 inches

**Unthreaded Mounting Hole Diameter:**

0.156 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Mounting Facility Type And Quantity:**

1 unthreaded mounting holes

**Features Provided:**

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:**

5000.0 megohm-microfarads

**Capacitance Value Per Section:**

2.200 microfarads single section

**Nonderated Operating Temp:**

Between -65.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

30.0 dc single section

**Tolerance Range Per Section:**

-5.00/+5.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

68000.0 megohm-microfarads

**Dissipation Factor At Reference Temperature In Percent:**

0.600

**Terminal Surface Treatment:**

Solder

**Dielectric Material:**

Plastic polyethylene terephthalate

**Test Data Document:**

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-19978/14 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0