

View Online at https://aerobasegroup.com/nsn/5910-01-281-6162

### **Body Style:**

W/o mtg facilities, radial terminals

## **Reliability Indicator:**

Not established

### **Body Diameter:**

0.228 inches

#### **Body Length:**

0.430 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Capacitance Value Per Section:

9.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-60.0/+60.0 single section

## **Tolerance Range Per Section:**

-0.50/+0.50 picofarads single section

## **Test Data Document:**

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

## **Specification Data:**

81349-mil-c-20/3 government specification

Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A010b0