Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-281-7658

# **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

5.000

### **Terminal Length:**

Between 1.500 inches and 2.500 inches

#### **Body Diameter:**

0.750 inches

**Body Length:** 

Between 2.324 inches and 2.406 inches

### **Capacitance Value Per Section:**

4.700 microfarads single section

### Nonderated Operating Temp:

85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

130.0 ac-rms single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

# **Case Material:**

Metal

### **Case Insulation Material:**

Plastic

## **Test Data Document:**

81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

## **Specification Data:**

81349-mil-c-39022/07 government specification

## Shelf Life:

N/a

#### Unit Of Measure:

```
--
```

Demilitarization:

No

Fiig:

A010b0