## NSN 5910-01-282-2030

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-282-2030

## **Body Style:**

W/o mtg facilities, terminal (s) on one end

## **Reliability Indicator:**

Not established

## **Terminal Length:**

0.063 inches

#### **Body Diameter:**

3.078 inches

#### **Body Length:**

4.750 inches

#### Center To Center Distance Between Terminals Parallel To Diameter:

1.250 inches

#### **Terminal Diameter:**

0.190 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Electrical Polarization:**

Polarized

## Capacitance Value Per Section:

6200.000 microfarads single section

## Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

## Dc Leakage At Maximum Operating Temp:

15000.0 microamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

150.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+50.00 percent single section

#### **Case Material:**

Metal

#### **Capacitive Electrode Material:**

Aluminum

#### Equivalent Series Resistance At Reference Tempurature In Ohms:

0.052

#### Dc Leakage At Reference Temp:

6000.000 microamperes

## **Terminal Surface Treatment:**

Solder

## **Case Insulation Material:**

Plastic

## **Terminal Type And Quantity:**

2 threaded hole

# NSN 5910-01-282-2030

Electrolytic Fixed Capacitor - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0

