NSN 5910-01-282-7177

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-282-7177 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.520 inches **Bushing Diameter:** 0.190 inches **Bushing Length:** 0.203 inches **Body Length:** Between 0.261 inches and 0.301 inches **Overall Diameter:** 0.220 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 10000.0 **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encased **Tuning Characteristic:** Straight line capacity single section **Adjustment Device Torque:** Between 0.500 inch-ounces and 6.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms **Insulation Dc Resistance At Max Operating Temp:** 100000.0 megohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 64 **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.190 inches

NSN 5910-01-282-7177

Air Dielectric Variable Capacitor - Page 2 of 2



Capacitance Range In Picofarads:
+0.6/+6.0 single section
Nonderated Voltage Rating And Type:
250.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Material:
Ceramic base
Test Data Document:
81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
1 printed circuit
Specification Data:
81349-mil-c-14409/12 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A096a0