NSN 5910-01-282-7853

Air Dielectric Variable Capacitor - Page 1 of 2



Thread Class: 2a Body Style: Plate-meshing Overall Length: 1.063 inches Terminal Length: 0.866 inches Overall Height: 1.969 inches Overall Width: 1.693 inches Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosure Type: Uninclosure Topic: Uning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life: N/a	
Body Style: Plate-meshing Overall Length: 1.063 inches Terminal Length: 0.866 inches Overall Height: 1.969 inches Overall Width: 1.693 inches Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	View Online at https://aerobasegroup.com/nsn/5910-01-282-7853
Body Style: Plate-meshing Overall Length: 1.063 inches Terminal Length: 0.866 inches Overall Height: 1.969 inches Overall Width: 1.693 inches Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Thread Class:
Plate-meshing Overall Length: 1.063 inches Terminal Length: 0.866 inches Overall Height: 1.969 inches Overall Width: 1.693 inches Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	2a
Overall Length: 1.063 inches Terminal Length: 0.866 inches Overall Height: 1.969 inches Overall Width: 1.693 inches Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Body Style:
1.063 inches Terminal Length: 0.866 inches Overall Height: 1.969 inches Overall Width: 1.693 inches Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Plate-meshing
Terminal Length: 0.866 inches Overall Height: 1.969 inches Overall Width: 1.693 inches Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Overall Length:
Overall Height: 1.969 inches Overall Width: 1.693 inches Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	1.063 inches
Overall Height: 1.969 inches Overall Width: 1.693 inches Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Terminal Length:
1.969 inches Overall Width: 1.693 inches Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	0.866 inches
Overall Width: 1.693 inches Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Overall Height:
Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	1.969 inches
Shaft Diameter: 0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Overall Width:
0.248 inches single shaft and 0.251 inches single shaft Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	1.693 inches
Shaft Length: 1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Shaft Diameter:
1.142 inches single shaft End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	0.248 inches single shaft and 0.251 inches single shaft
End Application: 5895-01-154-3796 receiver-transm Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Shaft Length:
Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	1.142 inches single shaft
Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	End Application:
Uniclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	5895-01-154-3796 receiver-transm
Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Mounting Facility Screw Thread Series Designator:
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Unc
Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Inclosure Type:
Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Uninclosed
Adjustment Device Rotation: 180.0 degrees clockwise Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Tuning Characteristic:
Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Straight line capacity single section
Mounting Facility Type And Quantity: 2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Adjustment Device Rotation:
2 threaded stud Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	180.0 degrees clockwise
Thread Size: 0.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Mounting Facility Type And Quantity:
O.138 inches Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	2 threaded stud
Shaft Type: Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Thread Size:
Round single shaft Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	0.138 inches
Capacitance Range In Picofarads: +8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Shaft Type:
+8.0/+140.0 single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Round single shaft
Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Capacitance Range In Picofarads:
1 shaft Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	+8.0/+140.0 single section
Terminal Type And Quantity: 1 tab, solder lug and 2 turret Shelf Life:	Adjustment Device Drive Type And Quantity:
1 tab, solder lug and 2 turret Shelf Life:	1 shaft
Shelf Life:	Terminal Type And Quantity:
	1 tab, solder lug and 2 turret
N/a	Shelf Life:
	N/a
Unit Of Measure:	Unit Of Measure:

--

NSN 5910-01-282-7853

Air Dielectric Variable Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A096a0