NSN 5910-01-283-9069

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-283-9069

Body Style:

W/mtg bracket, axial terminals

Reliability Indicator:

Not established

Terminal Length:

Between 3.250 inches and 3.375 inches

Body Diameter:

Between 0.745 inches and 0.765 inches

Body Length:

Between 2.000 inches and 2.062 inches

Unthreaded Mounting Hole Diameter:

Between 0.151 inches and 0.161 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Internal Electrical Connection Type:

Extended foil

End Application:

6115-01-150-4140

Mounting Facility Type And Quantity:

1 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

25000.0 megohms

Capacitance Value Per Section:

0.100 microfarads single section

Nonderated Operating Temp:

Between -65.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.600

Dielectric Material:

Plastic polyethylene terephthalate

Terminal Type And Quantity:

1 insulated wire lead w/terminal lug

NSN 5910-01-283-9069

Plastic Dielectric Fixed Capacitor - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0