

View Online at https://aerobasegroup.com/nsn/5910-01-283-9081

D	
Body S	-
Chip typ	
	lity Indicator:
	ablished
	al Length:
0.015 ir	
Body L	-
	n 0.170 inches and 0.190 inches
Body V	
Betwee	n 0.070 inches and 0.090 inches
Body H	leight:
0.065 ir	nches
Schem	atic Diagram Designator:
No com	mon or grounded electrode (s)
End Ap	plication:
5820-07	I-221-3440 radio set
Insulat	ion Resistance At Maximum Operating Temp:
10000.0) megohms
Capaci	tance Value Per Section:
220000	.000 picofarads single section
Voltage	Tempurature Limits Per Section In Percent Capacitance Change:
-15.0/+*	15.0 without voltage applied single section
Nonder	rated Operating Temp:
Betwee	n -55.0 degrees celsius and 125.0 degrees celsius
Nonder	ated Continuous Voltage Rating And Type Per Section:
50.0 dc	single section
Tolerar	nce Range Per Section:
-5.00/+	5.00 percent single section
Case M	aterial:
Cerami	
Insulat	ion Resistance At Reference Temp:
100000	.0 megohms
Dissipa	tion Factor At Reference Tempurature In Percent:
2.500	
Termin	al Surface Treatment:
Solder	
Termin	al Type And Quantity:
2 bondi	ng pad
Shelf L	ife:
N/a	
Unit Of	Measure:



Demilitarization:

No

Fiig:

A010b0