## NSN 5910-01-284-2829

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-284-2829 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 40.0 millimeters **Body Diameter:** 6.5 millimeters **Body Length:** 17.5 millimeters **Terminal Diameter:** 0.6 millimeters **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Etched foil **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 47.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section **Tolerance Range Per Section:** -10.00/+50.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent: Equivalent Series Resistance At Reference Tempurature In Ohms:** 4.70 Dc Leakage At Reference Temp: 26.000 microamperes **Terminal Surface Treatment:** 

Solder **Case Insulation Material: Plastic Terminal Type And Quantity:** 2 uninsulated wire lead

## NSN 5910-01-284-2829

Electrolytic Fixed Capacitor - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0