NSN 5910-01-286-6390

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-286-6390 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Diameter:** Between 0.170 inches and 0.201 inches **Body Length:** 0.610 inches **Terminal Diameter:** Between 0.019 inches and 0.025 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 1.500 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 5.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 microfarads all sections Case Material: Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** Dc Leakage At Reference Temp: 0.250 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:**

Plastic

NSN 5910-01-286-6390

Electrolytic Fixed Capacitor - Page 2 of 2



Ferminal Type A	and Q	uantity:
-----------------	-------	----------

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0