NSN 5910-01-287-6626

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-287-6626

Body Style: W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.787 inches **Body Diameter:** 0.394 inches **Body Length:** 0.492 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.197 inches **Terminal Diameter:** 0.023 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Electrical Polarization:** Polarized **End Application:** 4920-01-187-4068 test system, aut **Capacitance Value Per Section:** 100.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 370.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 10.000 **Equivalent Series Resistance At Reference Tempurature In Ohms:**

Dc Leakage At Reference Temp:

4.000 microamperes

NSN 5910-01-287-6626

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0