NSN 5910-01-287-8465

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-287-8465

| Body Style: |
|---|
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.500 inches |
| Body Length: |
| 0.420 inches |
| Body Width: |
| 0.330 inches |
| Body Height: |
| 0.180 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.300 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| End Application: |
| 4920-01-187-4068 |
| Insulation Resistance At Maximum Operating Temp: |
| 10000.0 megohms |
| Capacitance Value Per Section: |
| 0.0068 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -1.00/+1.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 50000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.300 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |

N/a

NSN 5910-01-287-8465

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| | • - | | | |
|----|-----|------|---------|---|
| In | ıŧ | ()t | Measure | • |
| | | | | |

--

Demilitarization:

No

Fiig:

A010b0