NSN 5910-01-287-8466

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-287-8466

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Body Length:
0.420 inches
Body Width:
0.330 inches
Body Height:
0.180 inches
Center To Center Distance Between Terminals Parallel To Length:
0.300 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
4920-01-187-4068
Insulation Resistance At Maximum Operating Temp:
10000.0 megohms
Capacitance Value Per Section:
0.068 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
50000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.300
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:

N/a

NSN 5910-01-287-8466

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0