NSN 5910-01-287-8467

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-287-8467

| Body Style: | | | | | |
|---|--|--|--|--|--|
| W/o mtg facilities terminal (s) on one surface | | | | | |
| Reliability Indicator: | | | | | |
| Not established | | | | | |
| Terminal Length: | | | | | |
| 0.500 inches | | | | | |
| Body Length: | | | | | |
| 0.550 inches | | | | | |
| Body Width: | | | | | |
| 0.460 inches | | | | | |
| Body Height: | | | | | |
| 0.300 inches | | | | | |
| Center To Center Distance Between Terminals Parallel To Length: | | | | | |
| 0.400 inches | | | | | |
| Terminal Diameter: | | | | | |
| 0.025 inches | | | | | |
| Schematic Diagram Designator: | | | | | |
| No common or grounded electrode (s) | | | | | |
| End Application: | | | | | |
| 4920-01-187-4068 | | | | | |
| Insulation Resistance At Maximum Operating Temp: | | | | | |
| 10000.0 megohms | | | | | |
| Capacitance Value Per Section: | | | | | |
| 0.680 microfarads single section | | | | | |
| Nonderated Operating Temp: | | | | | |
| Between -55.0 degrees celsius and 85.0 degrees celsius | | | | | |
| Nonderated Continuous Voltage Rating And Type Per Section: | | | | | |
| 50.0 dc single section | | | | | |
| Tolerance Range Per Section: | | | | | |
| -1.00/+1.00 percent single section | | | | | |
| Case Material: | | | | | |
| Plastic | | | | | |
| Insulation Resistance At Reference Temp: | | | | | |
| 50000.0 megohms | | | | | |
| Dissipation Factor At Reference Tempurature In Percent: | | | | | |
| 0.300 | | | | | |
| Terminal Surface Treatment: | | | | | |
| Solder | | | | | |
| Terminal Type And Quantity: | | | | | |
| 2 uninsulated wire lead | | | | | |
| Shelf Life: | | | | | |

N/a

NSN 5910-01-287-8467

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A010b0