## NSN 5910-01-287-9194

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-287-9194

**Body Style:** 

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

**Body Length:** 

Between 0.180 inches and 0.200 inches

**Body Width:** 

Between 0.180 inches and 0.200 inches

**Body Height:** 

Between 0.080 inches and 0.100 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.185 inches and 0.215 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**End Application:** 

6610-01-194-8659 indicator, attit

**Insulation Resistance At Maximum Operating Temp:** 

700.0 megohm-microfarads

**Capacitance Value Per Section:** 

0.100 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Range Per Section:** 

-1.00/+1.00 percent single section

**Case Material:** 

Plastic

**Insulation Resistance At Reference Temp:** 

100000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

0.300

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-01-287-9194

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0