NSN 5910-01-291-1613

Glass Dielectric Variable Capacitor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5910-01-291-1613



Body Style: Piston **Overall Length:** 0.405 inches **Terminal Length:** 0.340 inches **Body Length:** 0.340 inches **Overall Diameter:** Between 0.430 inches and 0.490 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -150.0/+150.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.220 inches **Terminal Width:** 0.031 inches **Terminal Thickness:** 0.015 inches **Inclosure Type: Encased Terminal Location:** Circumference on adjustment control end bent backward **Adjustment Device Torque:** Between 0.500 inch-ounces and 5.000 inch-ounces **Insulation Dc Resistance At Max Operating Temp:** 10000.0 megohms **Mounting Facility Type And Quantity:** 3 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.5/+10.0 single section **Nonderated Voltage Rating And Type:** 250.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Terminal Type And Quantity:** 2 printed circuit and 1 turret Shelf Life:

N/a

NSN 5910-01-291-1613

Glass Dielectric Variable Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A096a0