

View Online at <https://aerobasegroup.com/nsn/5910-01-291-4011>

**Body Style:**

Chip type

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.100

**Body Length:**

0.265 inches

**Body Width:**

0.110 inches

**Body Height:**

0.110 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

10.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

25.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Capacitive Electrode Material:**

Tantalum

**Test Data Document:**

81349-mil-c-55365 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 bonding pad

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0