NSN 5910-01-291-6320

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-291-6320

view Offilitie at https://defobasegroup.com/nsi//0310-01-231-0320
Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
0.390 inches
Body Diameter:
0.177 inches
Body Length:
0.280 inches
Center To Center Distance Between Terminals Parallel To Diameter:
Between 0.070 inches and 0.130 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Impedance At Minimum Operating Tempurature In Ohms:
37.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
0.470 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
35.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
4.000
Dc Leakage At Reference Temp:
1.000 microamperes
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-291-6320

Electrolytic Fixed Capacitor - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0