NSN 5910-01-292-2042

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-292-2042 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 6.0 millimeters **Body Length:** 26.5 millimeters **Body Width:** 15.5 millimeters **Body Height:** 7.5 millimeters Center To Center Distance Between Terminals Parallel To Length: 22.5 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Capacitance Value Per Section:** 2200.000 picofarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -250.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 600.0 ac-rms single section and 2000.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.030 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polypropylene **Terminal Type And Quantity:**

Shelf Life:

N/a

2 uninsulated wire lead

NSN 5910-01-292-2042

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0