NSN 5910-01-293-0100

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-293-0100
Body Style:
Piston
Overall Length:
1.211 inches
Terminal Length:
0.500 inches
Body Length:
1.000 inches
Overall Diameter:
Between 0.844 inches and 0.906 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
0.0 single section
Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:
+0.0/+50.0 single section
Center To Center Distance Between Terminals Parallel To Length:
Between 0.844 inches and 0.906 inches
Terminal Diameter:
0.025 inches
Quality Factor At 25 Deg Celsius:
1500.0
Inclosure Type:
Encased
Insulation Dc Resistance At Max Operating Temp:
1000000.0 megohms
Mounting Facility Type And Quantity:
4 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 150.0 degrees celsius
Capacitance Range In Picofarads:
+0.6/+9.5 single section
Nonderated Voltage Rating And Type:
750.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Capacitance Drift In Picofarads:
0.01 single section
Material:
Glass base
Test Data Document:
81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

NSN 5910-01-293-0100

Glass Dielectric Variable Capacitor - Page 2 of 2



81349-mil-c-14409/7 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0