## NSN 5910-01-293-0100

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-293-0100
Body Style:
Piston
Overall Length:
1.211 inches
Terminal Length:
0.500 inches
Body Length:
1.000 inches
Overall Diameter:
Between 0.844 inches and 0.906 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
0.0 single section
Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:
+0.0/+50.0 single section
Center To Center Distance Between Terminals Parallel To Length:
Between 0.844 inches and 0.906 inches
Terminal Diameter:
0.025 inches
Quality Factor At 25 Deg Celsius:
1500.0
Inclosure Type:
Encased
Insulation Dc Resistance At Max Operating Temp:
1000000.0 megohms
Mounting Facility Type And Quantity:
4 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 150.0 degrees celsius
Capacitance Range In Picofarads:
+0.6/+9.5 single section
Nonderated Voltage Rating And Type:
750.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Capacitance Drift In Picofarads:
0.01 single section
Material:
Glass base
Test Data Document:
81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

## NSN 5910-01-293-0100

Glass Dielectric Variable Capacitor - Page 2 of 2



81349-mil-c-14409/7 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A096a0