## NSN 5910-01-294-1967

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-294-1967

| Body Style:  |
|--|
| N/o mtg facilities, axial terminals  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.100  |
| Terminal Length:   |
| 1.625 inches   |
| Body Diameter:   |
| 0.562 inches   |
| Body Length:   |
| 1.375 inches   |
| Terminal Diameter:   |
| 0.040 inches   |
| Schematic Diagram Designator:  |
| No common or grounded electrode (s)  |
| Features Provided:   |
| Hermetically sealed case   |
| Capacitance Value Per Section:   |
| 0.330 microfarads single section   |
| Nonderated Operating Temp:   |
| Between -65.0 degrees celsius and 100.0 degrees celsius  |
| Nonderated Continuous Voltage Rating And Type Per Section:   |
| 400.0 dc single section  |
| Tolerance Range Per Section:   |
| 1.00/+1.00 percent single section  |
| Case Material:   |
| Metal  |
| Case Insulation Material:  |
| Plastic  |
| Test Data Document:  |
| 31349-mil-c-83421 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Terminal Type And Quantity:  |
| 2 uninsulated wire lead  |
| Specification Data:  |
| 31349-mil-c-83421/1 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del>-</del>   |

No

Demilitarization:

## NSN 5910-01-294-1967

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0