

View Online at https://aerobasegroup.com/nsn/5910-01-295-2840

## Body Style:

W/o mtg facilities, terminals on opposite surfaces

## **Reliability Indicator:**

Not established

# Terminal Length:

Between 1.500 inches and 2.500 inches

#### **Body Length:**

Between 1.850 inches and 1.950 inches

#### **Body Width:**

Between 0.650 inches and 0.750 inches

#### **Body Height:**

Between 0.820 inches and 0.920 inches

#### **Terminal Diameter:**

0.032 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

4000.0 megohm-microfarads

#### **Capacitance Value Per Section:**

10.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

40000.0 megohm-microfarads

#### **Dissipation Factor At Reference Tempurature In Percent:**

1.000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

# NSN 5910-01-295-2840 Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



**Fiig:** A010b0