## NSN 5910-01-295-4482



| Electrolytic Fixed Capacitor - Page 1 of 2                                   |
|--|
| View Online at https://aerobasegroup.com/nsn/5910-01-295-4482                |
| Body Style:  |
| W/o mtg facilities, terminal (s) on one surface                              |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| 0.594 inches   |
| Body Length:   |
| 3.125 inches   |
| Body Width:  |
| 1.000 inches   |
| Body Height:   |
| 5.000 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.120 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| Between 1.469 inches and 1.531 inches  |
| Schematic Diagram Designator:  |
| No common or grounded electrode (s)  |
| Anode Type:  |
| Plain foil   |
|  |

**Electrical Polarization:** 

Polarized

**Mounting Facility Type And Quantity:** 

2 unthreaded mounting holes

**Features Provided:** 

Hermetically sealed case

**Capacitance Value Per Section:** 

940.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:** 

200.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

Dc Leakage At Reference Temp:

330.000 microamperes

**Terminal Surface Treatment:** 

Solder

## NSN 5910-01-295-4482

Electrolytic Fixed Capacitor - Page 2 of 2



| <b>Special</b> | Features: |
|----------------|-----------|
|----------------|-----------|

Uninsulated shorting wire supplied

**Terminal Type And Quantity:** 

2 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0