NSN 5910-01-296-6679

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-296-6679 **Body Style: Dual inline Reliability Indicator:** Not established **Terminal Length:** 0.120 inches **Body Length:** 0.200 inches **Body Width:** Between 0.240 inches and 0.280 inches **Body Height:** 0.180 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.090 inches and 0.110 inches **Center To Center Distance Between Terminals Parallel To Width:** Between 0.325 inches and 0.375 inches **Schematic Diagram Designator:** Two common terminals for each electrode **Anode Type:** Solid **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 6.800 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: **Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 6.000 Dc Leakage At Reference Temp: 4.700 microamperes **Terminal Surface Treatment:**

Solder

Terminal Type And Quantity:

4 printed circuit

NSN 5910-01-296-6679

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0