NSN 5910-01-296-7528

Body Style:

2 bonding pad

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-296-7528

Chip type
Reliability Indicator:
Not established
Terminal Length:
0.020 inches
Body Length:
0.080 inches
Body Width:
0.050 inches
Body Height:
0.050 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
5820-01-221-3440 radio set
Insulation Resistance At Maximum Operating Temp:
10000.0 megohms
Capacitance Value Per Section:
7.500 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
rempurature obenicient of capacitance i er dection in i pin i er beg delsids.
0.0 single section
0.0 single sectionNonderated Continuous Voltage Rating And Type Per Section:50.0 dc single section
 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section:
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Case Material:
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Case Material: Ceramic
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Case Material: Ceramic Insulation Resistance At Reference Temp:
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.100
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.100 Terminal Surface Treatment:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.100 Terminal Surface Treatment: Palladium and silver
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.100 Terminal Surface Treatment: Palladium and silver Precious Material And Location:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.100 Terminal Surface Treatment: Palladium and silver

NSN 5910-01-296-7528

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Shelf L	₋ife:
---------	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0