## NSN 5910-01-296-7534

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-296-7534

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
Between 0.197 inches and 0.236 inches
Body Length:
0.418 inches
Body Width:
0.359 inches
Body Height:
0.162 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.285 inches and 0.315 inches
Terminal Diameter:
0.024 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.010 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
10000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.000
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polyester
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5910-01-296-7534

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0