NSN 5910-01-298-5218

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-298-5218

| Body Style: |
|--|
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 2.000 inches |
| Body Diameter: |
| 0.280 inches |
| Body Length: |
| 0.650 inches |
| Terminal Diameter: |
| 0.020 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 1.200 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Range Per Section: |
| -2.00/+2.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 20000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 1.000 |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A010b0 |