## NSN 5910-01-299-4462

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-299-4462 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** Between 0.433 inches and 0.591 inches **Body Length:** 0.749 inches **Body Width:** 0.591 inches **Body Height:** 0.354 inches Center To Center Distance Between Terminals Parallel To Length: 0.600 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 1.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 100.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic** Insulation Resistance At Reference Temp: 25000.0 megohms **Dissipation Factor At Reference Tempurature In Percent: Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyethylene terephthalate

**Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:** 

## NSN 5910-01-299-4462

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	$\sim$	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ı		

No

Fiig:

A010b0