NSN 5910-01-299-6269

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-299-6269

view Offiline at https://acrobasegroup.com/histi/0310-01-233-0203
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Diameter:
0.592 inches
Body Length:
1.407 inches
Terminal Diameter:
0.040 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
End Application:
Countermeasures set an/alq-135b
Features Provided:
Burn in
Insulation Resistance At Maximum Operating Temp:
500000.0 megohms
Capacitance Value Per Section:
0.082 microfarads single section
Nonderated Operating Temp:
Between -65.0 degrees celsius and 100.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
600.0 ac-rms single section and 800.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
1000000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.200
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polycarbonate
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:

N/a

NSN 5910-01-299-6269

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
ш	ın	ıt (r 1t	ΝЛ	മാ	CI.	ıre:	•

--

Demilitarization:

No

Fiig:

A010b0