NSN 5910-01-299-6345

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-299-6345 **Body Style:** Rotary **Terminal Length:** 0.118 inches **Overall Height:** 0.217 inches **Overall Diameter:** 0.205 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: -1400.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -700.0/+700.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.200 inches **Unthreaded Mounting Hole Diameter:** 0.047 inches **End Application:** 4920-01-187-4068 test system, aut **Inclosure Type: Encased Split-stator Rotary Plate Type:** Differential **Adjustment Device Torque:** Between 0.400 inch-ounces and 2.500 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms **Mounting Facility Type And Quantity:** 2 unthreaded hole **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +5.0/+25.0 single section **Nonderated Voltage Rating And Type:** 250.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Terminal Type And Quantity:** 2 printed circuit Shelf Life: N/a **Unit Of Measure:**

--

NSN 5910-01-299-6345

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A096a0