## NSN 5910-01-300-1508

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-300-1508

**Body Style:** 

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

**Body Length:** 

0.250 inches

**Body Width:** 

0.220 inches

0.220 1101103

Body Height:

0.200 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.140 inches and 0.200 inches

**Terminal Diameter:** 

Between 0.023 inches and 0.027 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**End Application:** 

Countermeasures set an/alq-135b

**Insulation Resistance At Maximum Operating Temp:** 

10000.0 megohms

**Capacitance Value Per Section:** 

4700.000 picofarads single section

Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

2.500

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-300-1508

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Shelf L	₋ife:
---------	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0