Air Dielectric Variable Capacitor - Page 1 of 2



E	Body Style:
F	Piston
C	Overall Length:
0	0.926 inches
Т	erminal Length:
0	0.500 inches
E	Body Length:
0	0.765 inches
C	Overall Diameter:
0	.285 inches
Т	empurature Coefficient Of Capacitance In Ppm Per Deg Celsius
0	0.0 single section
Т	olerance Of Tempurature Coefficient In Ppm Per Deg Celsius:
-;	30.0/+30.0 single section
G	Quality Factor At 25 Deg Celsius:
8	00.0
h	nclosure Type:
E	Incased
Т	uning Characteristic:
S	Straight line capacity single section
A	Adjustment Device Torque:
E	Between 1.000 inch-ounces and 5.000 inch-ounces
Ν	Iounting Facility Type And Quantity:
4	terminal
N	Ionderated Operating Temp:
E	Between -65.0 degrees celsius and 125.0 degrees celsius
C	Capacitance Range In Picofarads:
+	1.0/+30.0 single section
Ν	londerated Voltage Rating And Type:
2	250.0 dc continuous single section
A	Adjustment Device Drive Type And Quantity:
1	slotted screw
N	Naterial:
Ν	letal base
Т	erminal Type And Quantity:
4	wire lead
S	Shelf Life:
Ν	l/a
ι	Jnit Of Measure:
C	Demilitarization:
	lo

NSN 5910-01-300-2276

Air Dielectric Variable Capacitor - Page 2 of 2

Fiig: A096a0

