## NSN 5910-01-301-9766

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-301-9766

**Body Style:** 

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

0.001

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

Between 0.557 inches and 0.587 inches

**Body Length:** 

Between 1.281 inches and 1.343 inches

**Terminal Diameter:** 

0.032 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

**Capacitance Value Per Section:** 

1.200 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-5.00/+5.00 percent single section

Case Material:

Metal

**Insulation Resistance At Reference Temp:** 

100.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.250

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Test Data Document:** 

81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

**Specification Data:** 

81349-mil-c-39022/10 government specification

## NSN 5910-01-301-9766

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0