NSN 5910-01-303-6834

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-303-6834

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.236 inches
Body Length:
0.709 inches
Body Width:
0.472 inches
Body Height:
0.236 inches
Terminal Diameter:
0.031 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.330 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 dc single section
250.0 dc single section
250.0 dc single section Tolerance Range Per Section:
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material:
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms Dissipation Factor At Reference Tempurature In Percent:
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.000
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Type And Quantity:
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Type And Quantity: 2 uninsulated wire lead
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
250.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: