NSN 5910-01-303-8753

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-303-8753

Body Style:					
W/o mtg facilities, terminals on opposite surfaces					
Reliability Indicator:					
Not established					
Terminal Length:					
1.500 inches					
Body Length:					
1.220 inches					
Body Width:					
0.490 inches					
Body Height:					
0.630 inches					
Terminal Diameter:					
0.032 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Insulation Resistance At Maximum Operating Temp:					
2000.0 megohm-microfarads					
Capacitance Value Per Section:					
0.330 microfarads single section					
Nonderated Operating Temp:					
Between -55.0 degrees celsius and 85.0 degrees celsius					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:					
Nonderated Continuous Voltage Rating And Type Per Section:					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section:					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material:					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohm-microfarads					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment:					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Dielectric Material:					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Dielectric Material: Plastic polyethylene terephthalate					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Dielectric Material: Plastic polyethylene terephthalate Terminal Type And Quantity:					
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Dielectric Material: Plastic polyethylene terephthalate Terminal Type And Quantity: 2 uninsulated wire lead					

--

NSN 5910-01-303-8753

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	tariz	

No

Fiig:

A010b0