

View Online at <https://aerobasegroup.com/nsn/5910-01-304-8728>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

0.250 inches

Body Diameter:

1.375 inches

Body Length:

3.120 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

Forrestal class cv, blue ridge class lcc-19, oliver perry class ffg, kilauea class t-ae 26, nimitz class cvn, ohio class ssn ship (trident).

General purpose electronic test equipment (gpete).

Capacitance Value Per Section:

75.000 microfarads single section

Nonderated Operating Temp:

Between -30.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-20.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

3.20

Case Insulation Material:

Plastic

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0