## NSN 5910-01-305-4330

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-305-4330

**Body Style:** 

W/thd bushing mtg, terminals on opposite ends

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 0.122 inches and 0.182 inches

**Unable To Decode:** 

Unable to decode and unable to decode

**Unable To Decode:** 

Unable to decode and unable to decode

**Body Diameter:** 

Between 0.365 inches and 0.385 inches

**Body Length:** 

Between 0.140 inches and 0.160 inches

**Terminal Diameter:** 

Between 0.030 inches and 0.050 inches

**Schematic Diagram Designator:** 

Feedthrough

**Mounting Facility Screw Thread Series Designator:** 

Wioaiit

Unf

**Mounting Facility Type And Quantity:** 

1 threaded bushing

**Capacitance Value Per Section:** 

0.120 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:** 

0.250 inches

Nonderated Continuous Voltage Rating And Type Per Section:

115.0 ac-rms single section and 300.0 dc single section

**Tolerance Range Per Section:** 

-0.00/+100.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

1000.0 megohms

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-01-305-4330

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A010b0