## NSN 5910-01-305-7150

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-305-7150

Rody	Style:	
Dogv	OLVIC.	

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 0.218 inches and 0.282 inches

**Body Diameter:** 

1.375 inches

**Body Length:** 

2.250 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

Between 0.285 inches and 0.315 inches

**Terminal Diameter:** 

Between 0.060 inches and 0.065 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

680.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+50.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.293

Dc Leakage At Reference Temp:

6000.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

3 pin

## NSN 5910-01-305-7150

Electrolytic Fixed Capacitor - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0