NSN 5910-01-306-2330

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-306-2330

Body Style:

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

Body Length:

Between 4.500 inches and 4.850 inches

Body Width:

Between 3.625 inches and 3.875 inches

Body Height:

Between 9.500 inches and 9.850 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 1.813 inches and 2.187 inches

Terminal Height From Body:

2.000 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Transmitting set, radio an/frt-96

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

2.5 megohms

Capacitance Value Per Section:

12.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 45.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

8000.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

250.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.000

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic polyethylene terephthalate

Terminal Type And Quantity:

2 standoff, threaded stud

NSN 5910-01-306-2330

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| Shelf | Life: |
|-------|-------|
| N/a | |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0