## NSN 5910-01-306-2330

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-306-2330

**Body Style:** 

W/o mtg facilities, terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Body Length:** 

Between 4.500 inches and 4.850 inches

**Body Width:** 

Between 3.625 inches and 3.875 inches

**Body Height:** 

Between 9.500 inches and 9.850 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 1.813 inches and 2.187 inches

**Terminal Height From Body:** 

2.000 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**End Application:** 

Transmitting set, radio an/frt-96

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

2.5 megohms

**Capacitance Value Per Section:** 

12.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 45.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

8000.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Metal

**Insulation Resistance At Reference Temp:** 

250.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

1.000

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Plastic polyethylene terephthalate

**Terminal Type And Quantity:** 

2 standoff, threaded stud

## NSN 5910-01-306-2330

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf	Life:
N/a	

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0