

View Online at <https://aerobasegroup.com/nsn/5910-01-306-2346>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

Between 0.062 inches and 0.125 inches

Body Diameter:

Between 3.000 inches and 3.093 inches

Body Length:

Between 5.625 inches and 6.062 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 1.219 inches and 1.281 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Impedance At Minimum Operating Temperature In Ohms:

12.0

Electrical Polarization:

Polarized

Features Provided:

Burn in

Capacitance Value Per Section:

1200.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

7.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

Tolerance Range Per Section:

-10.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Temperature In Percent:

18.000

Equivalent Series Resistance At Reference Temperature In Ohms:

0.165

Dc Leakage At Reference Temp:

2.070 milliamperes

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0