

View Online at <https://aerobasegroup.com/nsn/5910-01-306-2346>

**Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.062 inches and 0.125 inches

**Body Diameter:**

Between 3.000 inches and 3.093 inches

**Body Length:**

Between 5.625 inches and 6.062 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

Between 1.219 inches and 1.281 inches

**Terminal Diameter:**

0.190 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Impedance At Minimum Operating Temperature In Ohms:**

12.0

**Electrical Polarization:**

Polarized

**Features Provided:**

Burn in

**Capacitance Value Per Section:**

1200.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

7.0 milliamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

400.0 dc single section

**Tolerance Range Per Section:**

-10.00/+50.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

18.000

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.165

**Dc Leakage At Reference Temp:**

2.070 milliamperes

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

2 threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0