NSN 5910-01-306-2795

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-306-2795 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 12.7 millimeters **Body Diameter:** 8.5 millimeters **Body Length:** 12.5 millimeters **Terminal Diameter:** 0.6 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Capacitance Value Per Section:** 1500.000 nanofarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 70.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -140.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 160.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -80.0/+80.0 single section **Tolerance Range Per Section:** -2.00/+2.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 25000.0 megohms **Power Factor At Reference Tempurature In Percent:** 0.001 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polystyrene **Terminal Type And Quantity:** 2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-01-306-2795

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0