## NSN 5910-01-306-8745

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-306-8745

**Body Style:** 

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

**Terminal Length:** 

Between 0.210 inches and 0.290 inches

**Body Diameter:** 

Between 1.180 inches and 1.219 inches

**Body Length:** 

Between 1.101 inches and 1.259 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.075 inches and 0.083 inches

Center To Center Distance Between Mounting Facilities Parallel To Diameter:

Between 0.390 inches and 0.398 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Electrical Polarization:** 

Polarized

**End Application:** 

6625-01-255-4547 voltmeter

**Mounting Facility Type And Quantity:** 

2 unthreaded mounting holes

**Capacitance Value Per Section:** 

3300.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+30.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 tab, solder lug

## NSN 5910-01-306-8745

Electrolytic Fixed Capacitor - Page 2 of 2



| She | lf I | Life: |
|-----|------|-------|
|     |      |       |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0